VARIO-HP Classic

carbonit°

■ DESCRIPTION:

Point-of-use under-counter water filtration for obtaining filtered drinking water. To be used with declared drinking water only. Very suitable for the preparation of beverages, water for cooking, etc.

■ AREA OF APPLICATION:

Preferably used in the kitchen. Install device under the basin between a corner valve and the existing water faucet with a tee branch. Mount the enclosed water faucet next to basin and connect for providing filtered water seperately.

■ TECHNICAL DATA:

Part no.:	120VHP-BS1
Measures:	Filter unit without connections (WxHxD): 123x310x115 mm; length of connection hoses: 2 pieces, each ca. 80 cm, 1 piece ca. 30 cm
Weight:	Complete dry ca. 2.4 kg (2.9 lbs), complete wet ca. 3.5 kg (4.6 lbs).
Material:	High-pressure housing up to 90 bar) made of Grilamid TR 90; casing top and screw of POM Hostaform C 2571; armoured flexible hoses
Flow:	Approx. 120 liters per hour with NFP Premium (standard) (at 4 bar, after 5 min. initial flow)
Filtration Performance:	For the removal of contaminants, see filter cart- ridge data sheets for NFP Premium (standard) or for desired cartridge.

OPERATION NOTE:

- → Mount short hose plus tee branch to corner valve, connect long hose and filterhousing to tee
- → Operate only with cold water! Protect from freezing.

■ COMPATIBLE CARTRIDGES:

Holds any CARBONIT® filter cartridge or standard 9 $\frac{3}{4}$ " cartridge (max. 72 mm diameter).



■ SCOPE OF SUPPLY:

Complete filter device with connection hoses, tee branch, shut-off valve, wall mounting and filter water faucet (type WS 8).

A CARBONIT® Monoblock NFP Premium filter cartridge is included.

■ AVAILABLE VERSIONS:

- → Double VARIO: optionally, if needed: add prefilter housing kit (120VHP-BS6OP) plus desired sediment prefilter cartridge (VFS 09)
- → VARIO Küche: rapid-coupling hose-connectors, no filter water faucet (for individual choice of additional faucet type)

